PENTAIR

# EVERPURE® CARTRIDGE REFERENCE GUIDE

| | | | | APPLICATIONS | | | | | | | | BENEFITS | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Product | System Part No. | Rated Capacity Gals / Liters | Micron Rating | Coffee | Espresso | Drinking Water | Iced Tea | Fountain | Ice | Boilerless Steam | Boiler Steam | Chlorine, Taste & Odor | Scale Inhibition | Particulate | Turbidity Reduction | Lead Reduction | Cyst Reduction* | Chloramines | Bacteriostatic* Control | Bacteria Reduction | NSF |
| 2CB5 | EV9617-05 | 3,000 / 11,355 | 5.0 | • | | • | | • | | | | • | | • | | | | | | | 42 |
| 2CB5-K | EV9617-06 | 3,000 / 11,355 | 5.0 | • | | • | | | | | | • | • | • | | | | | • | | 42 |
| 2CB5-S | EV9617-22 | 3,000 / 11,355 | 5.0 | • | | • | • | | | | | • | • | • | | | | | | | 42 |
| 2CB-GW | EV9618-36 | 3,000 / 11,355 | 10 | • | | | | | | | | • | • | • | | | | | | | N/A |
| 2FC | EV9691-56 | 6,000 / 22,710 | 0.5 | | | • | | | | | | • | | • | • | | • | | • | | 42, 53 |
| 2FC-S | EV9691-76 | 6,000 / 22,710 | 0.5 | • | | • | • | | | | | • | • | • | • | | • | | • | | 42, 53 |
| 2FC5 | EV9691-66 | 6,000 / 22,710 | 5.0 | | | • | | • | | | | • | | | | | | | • | | 42 |
| 2FC5-S | EV9691-86 | 6,000 / 22,710 | 5.0 | • | | | | | • | | | • | • | | | | | | • | | 42 |
| 2H-L | EV9634-26 | 750 / 2,839 | 0.5 | | | • | | | | | | • | • | • | | • | • | | | | 42, 53 |
| 4C[2] | EV9605-50 | 3,900 / 14,763 | 0.5 | | | • | | • | | | | • | | • | | | • | | • | | 42, 53 |
| 4CB5 | EV9617-16 | 6,000 / 22,710 | 5.0 | | | • | | • | | • | • | • | | • | | | | | | | 42 |
| 4CB5-K | EV9617-36 | 6,000 / 22,710 | 5.0 | • | | • | | | | | | • | • | • | | | | | • | | 42 |
| 4CB5-S | EV9617-26 | 6,000 / 22,710 | 5.0 | • | | • | | | • | | | • | • | • | | | | | | | 42 |
| 4FC | EV9692-21 | 15,000 / 56,781 | 0.5 | | | • | | • | | | | • | | • | | | • | | • | | 42, 53 |
| 4FC-S | EV9692-31 | 15,000 / 56,781 | 0.5 | • | | | | | • | | | • | • | • | | | • | | • | | 42, 53 |
| 4FC5 | EV9693-21 | 15,000 / 56,781 | 5.0 | | | • | | • | | | | • | | • | | | | | • | | 42 |
| 4FC5-S | EV9693-31 | 15,000 / 56,781 | 5.0 | • | | | | | • | | | • | • | • | | | | | • | | 42 |
| 4FC-L | EV9693-10 | 4,900 / 18,548 | 0.5 | | | • | | • | | | | • | | • | • | • | • | | | | 42, 53 |
| 4FC-LS | EV9693-16 | 4,900 / 18,548 | 0.5 | • | | • | | | • | | | • | • | • | • | • | • | | | | 42, 53 |
| 4H[2] | EV9605-70 | 3,900 / 14,763 | 0.5 | • | | • | | | | | | • | • | • | | | • | | • | | 42, 53 |
| 4H-L | EV9635-26 | 1,000 / 3,785 | 0.5 | | | • | | | | | | • | • | • | | • | • | | | | 42, 53 |
| 4SI | EV9606-51 | 15,000† / 56,781† | 0.5 | | | | | | • | | | | • | • | | | • | | | | 42, 53 |
| 7CB5 | EV9618-11 | 10,000 / 37,850 | 5.0 | | | | | • | | • | • | • | | • | | | | | | | 42 |
| 7BC5-K | EV9617-76 | 10,000 / 37,850 | 5.0 | • | | • | | | • | | | • | • | • | | | | | | | 42 |
| 7CB5-S | EV9618-21 | 10,000 / 37,850 | 5.0 | • | | | | | • | | | • | • | • | | | | | | | 42 |
| 7CLM+ | EV9771-00 | 7,500 / 28,391 | 5.0 | | | • | | • | | | | • | | • | | | • | • | | | 42 |
| 7FC | EV9692-61 | 25,000 / 94,635 | 0.5 | | | • | | • | | | | • | | • | | | • | | • | | 42, 53 |
| 7FC-L | EV9693-40 | 7,400 / 28,012 | 0.5 | | | • | | • | | | | • | | • | • | • | • | | • | | 42, 53 |

* Harmful cyst and microbial reduction by mechanical means. For further information concerning FIFRA registration, see product specification sheets.
† Estimated. Actual capacity may vary depending on volume of particulate in incoming water.
Note: See individual system specification sheets for performance claims and FIFRA registration information.