PENTAIR

EVERPURE® SYSTEM REFERENCE GUIDE

					APPLICATIONS										BENEFITS										
Product	System Part No.	Flow Rate GPM / LPM	Rated Capacity Gals/Liters	Micron Rating	Coffee	Espresso	Fountain	Drinking Water	Iced Tea	Frozen Carbonated Beverage (FBC)	Ice	Boilerless Steam	Boiler Steam	Warewashing	Chlorine, Taste & Odor	Chloramines	Scale Inhibition	Scale Reduction	Particulate	Total Dissolved Solids (TDS)	Mineral Boost	Mineral Blending	Cyst Reduction‡	Bacteriostatic‡	NSF
QL2-OCS[2]	EV9275-60	0.50 / 1.89	1,500 / 5,678	0.5	•										•		•		•				•	•	42, 53
QL3-BH[2]	EV9272-00	0.50 / 1.89	3,000 / 11,636	0.5	•										•		•		•				•	•	42, 53
QC7I Single-MH[2]*	*	1.67 / 6.32	9,000 / 34,907	0.5	•										•		•		•				•	•	42, 53
QC7I Twin-MH[2]	*	3.34 / 12.64	18,000 / 69,813	0.5	•										•		•		•				•	•	42, 53
QC7I Single-ESO6	*	0.50 / 1.89	409† / 1,586	5.0		•									•			•	•						–
QC7I Single-ESO7	*	0.50 / 1.89	531† / 2,059	5.0		•									•			•	•						–
QC7I Twin-ESO7	*	1.00 / 3.79	1,062† / 4,119	5.0		•									•			•	•						–
QC7I Triple-ESO7	*	1.50 / 5.68	1,593† / 6,178	5.0		•									•			•	•						–
QC7I Single-MC[2]	EV9275-01	1.67 / 6.32	9,000 / 34,907	0.5			•	•		•					•				•				•	•	42, 53
QC7I Twin-MC[2]	EV9275-02	3.34 / 12.64	18,000 / 69,813	0.5			•	•		•					•				•				•	•	42, 53
QC7I Triple-MC[2]	EV9275-03	5.00 / 18.93	27,000 / 104,720	0.5			•	•		•					•				•				•	•	42, 53
QC7I Quad-MC[2]	*	6.70 / 25.36	36,000 / 139,626	0.5			•	•		•					•				•				•	•	42, 53
QC7I Single-7CLM+	EV9771-11	1.67 / 6.32	7,500 / 28,391	5.0			•	•		•					•	•			•						42
QC7I Twin-7CLM+	EV9771-12	3.34 / 12.64	15,000 / 56,781	5.0			•	•		•					•	•			•						42
QC7I Triple-7CLM+	EV9771-13	5.01 / 18.96	22,500 / 85,172	5.0			•	•		•					•	•			•						42
QC7I Quad-7CLM+	EV9771-14	6.68 / 25.29	30,000 / 113,562	5.0			•	•		•					•	•			•						42
QC7I Single-XCLM+	EV9761-11	2.00 / 7.57	9,300 / 35,204	5.0			•	•		•					•	•			•						42
QC7I Twin-XCLM+	EV9761-12	4.00 / 15.14	18,600 / 70,409	5.0			•	•		•					•	•			•						42
QC7I Triple-XCLM+	EV9761-13	6.00 / 22.71	27,900 / 105,613	5.0			•	•		•					•	•			•						42
QC7I Quad-XCLM+	EV9761-14	8.00 / 30.28	37,200 / 140,817	5.0			•	•		•					•	•			•						42
Coldrink® 1-MC[2]	EV9328-01	1.67 / 6.32	9,000 / 34,907	0.5			•	•		•					•				•				•	•	42, 53
Coldrink 2-MC[2]	EV9328-02	3.34 / 12.64	18,000 / 69,813	0.5			•	•		•					•				•				•	•	42, 53
Coldrink 3 -MC[2]	EV9328-03	5.00 / 18.93	27,000 / 104,720	0.5			•	•		•					•				•				•	•	42, 53
Coldrink 4-4FC	EV9328-44	10.00 / 37.85	60,000 / 232,710	0.5			•	•		•					•				•				•	•	42, 53
Coldrink 3-7FC	EV9328-73	7.50 / 28.39	75,000 / 290,888	0.5			•	•		•					•				•				•	•	42, 53
Coldrink 4-7FC	EV9328-74	10.00 / 37.85	100,000 / 387,850	0.5			•	•		•					•				•				•	•	42, 53
Coldrink 1-7CLM+	EV9771-21	1.67 / 6.32	7,500 / 28,391	5.0			•	•		•					•	•			•						42
Coldrink 2-7CLM+	EV9771-22	3.34 / 12.64	15,000 / 56,781	5.0			•	•		•					•	•			•						42
Coldrink 3-7CLM+	EV9771-23	5.01 / 18.96	22,500 / 85,172	5.0			•	•		•					•	•			•						42
Coldrink 4-7CLM+	EV9771-24	6.68 / 25.29	30,000 / 113,562	5.0			•	•		•					•	•			•						42
Coldrink 1-XCLM+	EV9761-21	2.00 / 7.57	9,300 / 35,204	5.0			•	•		•					•	•			•						42
Coldrink 2-XCLM+	EV9761-22	4.00 / 15.14	18,600 / 70,409	5.0			•	•		•					•	•			•						42
Coldrink 3-XCLM+	EV9761-23	6.00 / 22.71	27,900 / 105,613	5.0			•	•		•					•	•			•						42
Coldrink 4-XCLM+	EV9761-24	8.00 / 30.28	37,200 / 140,817	5.0			•	•		•					•	•			•						42
Insurice® PF Single i2000[2]	EV9324-21	1.67 / 6.32	9,000 / 34,907	0.5							•				•		•		•				•	•	42, 53
Insurice Single-i2000[2]	EV9324-01	1.67 / 6.32	9,000 / 34,907	0.5							•				•		•		•				•	•	42, 53
Insurice PF Twin i2000[2]	EV9324-22	3.34 / 12.64	18,000 / 69,813	0.5							•				•		•		•				•	•	42, 53
Insurice Twin-i2000[2]	EV9324-02	3.34 / 12.64	18,000 / 69,813	0.5							•				•		•		•				•	•	42, 53

* Head and filter cartridge sold separately.
† Based on 10 grains of hardness (with Claris, a bypass setting of 4).
‡ Harmful cyst and microbial reduction by mechanical means. For further information concerning FIFRA registration, see product specification sheets.