PENTAIR

EVERPURE® SYSTEM REFERENCE GUIDE

					APPLICATIONS										BENEFITS										
Product	System Part No.	Flow Rate GPM / LPM	Rated Capacity Gals/Liters	Micron Rating	Coffee	Espresso	Fountain	Drinking Water	Iced Tea	Frozen Carbonated Beverage (FBC)	Ice	Boilerless Steam	Boiler Steam	Warewashing	Chlorine, Taste & Odor	Chloramines	Scale Inhibition	Scale Reduction	Particulate	Total Dissolved Solids (TDS)	Mineral Boost	Mineral Blending	Cyst Reduction*	Bacteriostatic*	NSF
Endurance® High Flow Twin	EV9437-30	7.50 / 28.39	100,000 / 387,850	0.5	•		•	•			•				•		•		•				•	•	42, 53
Endurance High Flow Triple	EV9437-31	11.25 / 42.59	150,000 / 581,775	0.5	•		•	•			•				•		•		•				•	•	42, 53
Endurance High Flow Quad	EV9437-32	15.00 / 56.78	200,000 / 775,700	0.5	•		•	•			•				•		•		•				•	•	42, 53
Endurance TKO MicroFilter	EV9437-50	15.00 / 56.78	NA	0.65															•						–
2SR-BW Endurance Feeder Kit	EV9798-70	NA	NA	NA	•						•		•				•								–
2SR-BW QL2 Feeder Kit	EV9798-75	NA	NA	NA	•						•		•				•								–
Endurance SC Twin	EV9437-40	7.50 / 28.39	100,000 / 378,541	0.5	•		•	•			•				•		•		•				•	•	42, 53
Endurance SC Triple	EV9437-41	11.25 / 42.59	150,000 / 567,812	0.5	•		•	•			•				•		•		•				•	•	42, 53
Endurance SC Quad	EV9437-42	15.00 / 56.78	200,000 / 757,082	0.5	•		•	•			•				•		•		•				•	•	42, 53
CB20-124E	EV9100-51	5.00 / 18.93	15,000 / 58,178	5.0			•	•		•					•	•			•						–
CB20-302E	EV9100-32	5.00 / 18.93	20,000 / 77,570	5.0			•	•		•					•	•			•						–
CB20-312E	EV9100-37	5.00 / 18.93	85,000 / 329,673	0.5			•	•		•					•	•			•				•		42, 53
LVRO-75HE	EV9975-00	NA	14.66 / 55.49	NA				•							•			•	•	•			•		58
LVRO-75HE+F	EV9975-10	NA	14.66 / 55.49	NA				•							•			•	•	•			•		58
Conserv® LT-S	EV9975-20	NA	50.51/191.20	NA								•			•			•	•	•	•	•			58
Conserv 75S	EV9976-00	NA	50.51 / 191.20	NA								•			•			•	•	•	•	•	•		58
Conserv 75E	EV9977-00	NA	50.51 / 191.20	NA	•	•									•			•	•	•	•	•	•		58
MRS-100	EV9970-07	NA	Up to 100 gpd†	NA	•	•						•	•		•			•	•	•					–
MRS-100BL	EV9970-73	NA	Up to 100 gpd†	NA	•	•						•	•		•			•	•	•		•			–
MRS-100CC-BL	EV9973-63	NA	Up to 100 gpd	NA	•	•			•			•	•		•			•	•	•	•	•	•		–
MRS-225	EV9970-08	NA	Up to 225 gpd	NA	•	•						•	•		•			•	•	•					–
MRS-225BL	EV9970-76	NA	Up to 225 gpd†	NA	•	•						•	•		•			•	•	•		•			–
MRS-225CC-BL	EV9970-19	NA	Up to 225 gpd†	NA	•	•			•			•	•		•			•	•	•	•	•	•		–
MRS-350	EV9970-17	NA	Up to 350 gpd	NA	•	•			•			•	•		•			•	•	•					–
MRS-350BL	EV9970-20	NA	Up to 350 gpd†	NA	•	•			•			•	•		•			•	•	•		•			–
MRS-350CC-BL	EV9973-65	NA	Up to 350 gpd†	NA	•	•			•			•	•		•			•	•	•	•	•	•		–
MRS-600HE	EV9970-38	NA	Up to 760 gpd†	NA	•	•			•			•	•		•			•	•	•		•		•	58
MRS-600HE-II	EV9970-54	NA	Up to 507 gpd†	NA	•	•			•			•	•		•			•	•	•		•		•	58
Kleensteam CT	EV9797-50	1.67 / 6.32	6,000 / 23,271	5.0									•		•		•		•						–
Kleensteam II Single	EV9797-21	2.50 / 9.46	10,000 / 38,785	5.0									•		•		•		•						–
Kleensteam II Twin	EV9797-22	5.00 / 18.93	20,000 / 77,570	5.0									•		•		•		•						–
SR-X Scale Inhibitor System	EV9797-20	6.00 / 22.71	NA	0.5	•						•		•				•								–

* Harmful cyst and microbial reduction by mechanical means. For further information concerning FIFRA registration, see product specification sheets.
† More with blend