PENTAIR

EVERPURE® SYSTEM REFERENCE GUIDE

					APPLICATIONS										BENEFITS							
Product	System Part No.	Flow Rate GPM / LPM	Rated Capacity Gals/Liters	Micron Rating	Coffee	Espresso	Fountain	Drinking Water	Iced Tea	Frozen Carbonated Beverage (FBC)	Ice	Boilerless Steam	Boiler Steam	Warewashing	Chlorine, Taste & Odor	Chloramines	Scale Inhibition	Scale Reduction	Particulate	Pre-filtration RO System	Post-filtration RO System	NSF
SX2-21	160-00350	1.5/5.7	15,000/56,775	0.5	•	•			•				•		•		•		•			42
SX2-22	160-50142	3/11.3	30,000/113,550	0.5	•	•			•				•		•		•		•			42
FX-11	160-50010	1.5/5.7	15,000/56,775	0.5	•	•	•	•	•	•		•	•		•				•		•	42
FX-12	160-50020	3/11.3	30,000/113,550	0.5	•	•	•	•	•	•		•	•		•				•		•	42
FXAF01-12B	160-50345	8.0/30	N/A	1															•	•		–
FXAF-12B	160-50340	8.0/30	N/A	5															•	•		–
FX-22	160-50025	3/11.3	30,000/113,550	0.5	•	•	•	•	•	•		•	•		•				•			42
FX-22P	160-50030	6/22.7	60,000/227,100	0.5	•	•	•	•	•	•		•	•		•				•			42
FX-22P+	160-50035	6/22.7	60,000/227,100	0.5	•	•	•	•	•	•		•	•		•				•			42
FXI-11	160-50105	1.5/5.7	15,000/56,775	0.5	•						•	•	•		•		•		•			42
FXI-12	160-50110	3/11.3	30,000/113,550	0.5	•						•	•	•		•		•		•			42
FXI-22	160-50115	3/11.3	30,000/113,550	0.5	•						•				•		•		•			42
FXI-22P	160-50120	6/22.7	60,000/227,100	0.5	•						•				•		•		•			42
FXI-22P+	160-50125	6/22.7	60,000/227,100	0.5	•						•				•		•		•			42
FX11+CR	160-50012	3/11.4	10,000/37,800	0.5								•	•		•	•			•			–
FXI11+CR	160-50185	3/11.4	10,000/37,800	0.5								•	•		•	•	•		•			–
FX-12B	160-50022	5/18.9	50,000/189,271	5	•	•	•	•	•	•					•				•		•	–
FX-21	160-50015	1.5/5.7	15,000/56,775	0.5	•	•	•	•	•	•					•				•			–
FXTS-11	160-50003	2/7.6	20,000/75,600	5							•						•		•			–
SX2-22B	160-50143	4/15.1	50,000/189,271	5	•	•			•				•		•		•		•			–